



Specifications

Power Rating @70 deg.C :	1/20W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	10 Ohms ~ 1MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	30V
Max. working voltage:	15V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1/16W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	2 Ohms ~ 5.6MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	50V
Max. working voltage:	25V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1/10W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	100V
Max. working voltage:	50V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1/8W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	300V
Max. working voltage:	150V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1/4W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	400V
Max. working voltage:	200V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1/3W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	400V
Max. working voltage:	200V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	3/4W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded voltage :	400V
Max. working voltage:	200V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com



Specifications

Power Rating @70 deg.C :	1W
Solderability:	95% min. coverage
Life:	+/- (1.0% + 0.05 Ohms)
Moisture Resistance :	+/- (0.5% + 0.05 Ohms)
Resistance to Soldering Heat :	+/- (1.0% + 0.05 Ohms)
High Temperature:	+/- (1.0% + 0.05 Ohms)
Short Time Overload :	+/- (1.0% + 0.05 Ohms)
Low Temperature Operation :	+/- (0.05% + 0.05 Ohms)
Thermal Shock :	+/- (0.05% + 0.05 Ohms)
Temperature Coefficient (by Type) :	+/- 100 ppm/deg.C
Resistance Range 5%, E-24:	1 Ohms ~ 10MOhms
Resistance Range 1%, E-96 :	10 Ohms ~ 1MOhms
Max. overloaded volatge :	400V
Max. working voltage:	200V
Derated to 0 load at :	+125 deg.C
Operating Temp. Range:	-55 deg. C to +125 deg.C
Bending Strength :	+/- (1.0% + 0.05 Ohms)

Spectrum Sales Corporation

27-B, Siddharth Chambers,7, 2nd floor, Appa Balwant Chowk, Pune - 411002, India
Tel: +91 20 24483804 / +91 20 24452467, Fax: +91 20 24456664
Email: orders.spectrum@gmail.com